



TruLINK™ LED Visual Communication Device RAM® Mount Installation Instructions

We thank you for purchasing the Custom Dynamics® TruLINK™ LED Visual Communication Device RAM® Mount. Our products utilize the latest technology and high quality components to ensure you the most reliable service. We offer one of the best warranty programs in the industry and we back our products with excellent customer support, if you have questions before or during installation of this product please call Custom Dynamics® at 1(800) 382-1388.

Part Numbers: CDVL-RAM

Package Contents:

- RAM® 1" Ball Mounts (2)
- RAM® DBL Socket (1)
- Screw (2)
- Washer (2)

Fitment: **Universal**

Use with TruLINK™ LED Visual Communication Device (CDVL-01) sold separately.

Installation:

- 1) Select best location to mount unit on vehicle.
- 2) Use one of the two enclosed RAM® ball mounts as a template and drill two holes using a drill and drill bit.

Note: Vehicle Mounting hardware not included.

- 3) Attach RAM® ball mount base to vehicle.
- 4) Take the second RAM® ball mount and secure to the two mounting holes at the bottom of TruLINK™ LED Visual Communication Device (with cradle mount removed). Use included mounting hardware.
- 5) Connect the two ball mounts together with the DBL socket by loosening the center knob. One side is spring loaded. Once the knob is loose, you can apply pressure to the spring side and slip the opposite DBL socket on to the ball. Install the second ball mount and turn the center knob until tight.
- 6) If using TruLINK™ LED Visual Communication Device, follow instructions included with TruLINK PN CDVL-01. Continue with step #11 after mounted.



EVERYTHING To Light Up Your Ride!®

Questions? Call us at: 1 (800) 382-1388 M-TH 8:30AM-5:30PM / FR 9:30AM-5:30PM EST